

SB4132SM_400V

drill press

- left/right rotation 2- step motor
- speed range 60-3480min-1
- features solid, polished base with T-nuts
- aluminum motor according IP54
- torsion-resistant, solid and polished steel column
- the worktable is tiltable from -45° to +45° and rotates 360° around table center and column
- spindle protection cover
- adjustable drill depth stop with scale for accurate drill depth control
- selection switch for CW/CCW-rotation
- 2-step motor

included in delivery: automatic chuck 1-16mm, B18



**YOUR
JOB.
OUR
TOOLS.**

SB4132SM_400V

drill press



technical details

motor power s6 in W	1500/2200
voltage	400V
table size in mm	475x420
max. height in mm	1710
base in mm	580x450
distance spindle-base in mm	1160
drilling spindle collet	MK4 / MT4
column diameter in mm	90 / 2,5
gross weight in kg	125
packaging width in mm	653
EAN code	9120039901961

motor power s1 in W	700/1100
total dimensions in mm	570x870x1710
outreach in mm	257
max. drilling performance in mm	32
spindle stroke in mm	120
max. distance spindle-table in mm	680
drilling spindle speed in min-1	(24) 60-3480
net weight in kg	120
packaging height in mm	333
packaging length in mm	1.450

**YOUR
JOB.
OUR
TOOLS.**