

TS250F_230V

panel saw

- stable and precise table saw with aluminium sliding table
- largely dimensioned, stable outrigger table
- smoothly running saw blade height and angle adjustment
- large and precision-ground grey cast iron table with extension
- cross cut fence tilts 45° (left/right) and extensible (1230 - 2275 mm)
- rip fence with quick release clamp
- saw blade tilt (90-45°)

included in delivery: T.C.T. (Tungsten-Carbide-Tipped) general purpose blade with \varnothing 254 x 30 x 3,0 mm- 36 teeth, sliding table, edging shoe, push stick, sliding wood, table extension / widening, extensible cross-cut fence



**YOUR
JOB.
OUR
TOOLS.**

TS250F_230V

panel saw



technical details

motor power s6 in W	2900
voltage	230V / 50Hz
table height in mm	900
sliding table in mm	1650 x 250
table extension in mm	405 x 210
total dimensions in mm	2180(-3225) x 2930 x 1150
max. trimming in mm	1250
max. cutting width at parallel fence in mm	640
sawblade speed in min-1	4000
sound pressure level in dB(A)	86,5
gross weight in kg	233
packaging width in mm	760
EAN code	9120039903927

motor power s1 in W	2100
table size in mm	800 x 350
suction port in mm	Ø 100 (Ø30)
outrigger table in mm	595 x 460
table widening in mm	800 x 320
max. cutting height 90° in mm	80
max. cutting height 45° in mm	50
sawblade in mm	254 (/30)
sound power level in dB(A)	95,7
net weight in kg	190
packaging height in mm	1.035
packaging length in mm	970

**YOUR
JOB.
OUR
TOOLS.**