

TS315VF2600_400V

panel saw

- solid and smoothly running rip fence with quick clamp and bar guided
- tiltable and height adjustable circular saw blade with scoring unit
- cast iron table with table extension in the back and left with support leg
- extractable fence with workpiece end stop
- support roller at outrigger table eases the work piece allocation
- strengthened machine body below the sliding table
- increases stability
- XL cutting width at rip fence with max.1260mm
- high quality 2-piece scoring saw blade included

included in delivery: scoring unit, 1x T.C.T. saw blade Ø315mm, 1x T.C.T. scoring blade Ø100mm, mitre gauge, parallel fence, telescopic fence



**YOUR
JOB.
OUR
TOOLS.**

TS315VF2600_400V

panel saw



technical details

motor power s6 in W	5100
voltage	400V
table extension in mm	500x310 /800x440
suction port in mm	100
outrigger table in mm	760x540
max. trimming in mm	2600
max. cutting width at parallel fence in mm	1200
scoring sawblade in mm	100
scoring unit speed in min-1	8500
net weight in kg	340
packaging height in mm	1.040
packaging length in mm	1.220

motor power s1 in W	3800
table size in mm	800x820
table height in mm	850
sliding table in mm	2600x270
max. cutting height 90° in mm	100
max. cutting height 45° in mm	75
sawblade in mm	315
sawblade speed in min-1	4500
sawblade swivel	0°-45°
gross weight in kg	370
packaging width in mm	765
EAN code	9120039902821

**YOUR
JOB.
OUR
TOOLS.**