

## VPS4222\_400V

vertical panel saw

- max. cutting capacity vertical 2200 mm
- max. cutting capacity horizontal 4200 mm
- saw unit:
  - power 3,0 kW
  - $n_{\text{mainsawblade}}: 4500 \text{ min}^{-1}$ ;  $n_{\text{scoringunit}}: 9500 \text{ min}^{-1}$
- main-sawblade:  $\text{Ø}250 \times 30 \times 3,5 \text{ mm}$  (T80); scoring saw blade:  $\text{Ø}80 \times 2,8\text{-}3,6$  (T20)
- working pressure pneumatic: 6-8bar
- max. cutting depth
  - wooden board (MDF): 60 mm
  - solid wood boards: 50 mm
  - thermoplastic foam boards : 60 mm
  - aluminium plates : 20 mm
  - drywall: 60 mm

**included in delivery:** Main and scoring saw blade



**YOUR  
JOB.  
OUR  
TOOLS.**

# VPS4222\_400V

vertical panel saw

## technical details

|                            |                    |                               |                  |
|----------------------------|--------------------|-------------------------------|------------------|
| motor power s1 in W        | 3000               | voltage                       | 400 V / 3 / 50Hz |
| total dimensions in mm     | 5250 x 1700 x 2970 | min. workpiece length in mm   | 530              |
| min. workpiece width in mm | 230                | sound pressure level in dB(A) | 89,2             |
| gross weight in kg         | 735                | net weight in kg              | 633              |
| packaging width in mm      | 200                | packaging length in mm        | 5.200            |
| packaging height in mm     | 2.600              | EAN code                      | 9120058379390    |

**YOUR  
JOB.  
OUR  
TOOLS.**