

D510F_230V

wood lathe

- precision tool for professionals, gray cast iron version
- variable speed control with mini frequency converter, therefore high torque at low speeds
- high standard of spindle concentricity
- single hand operation of the tailstock and tool rest with cam lock mechanism
- metal handles are treated with chrome polish
- spindle fixable all 15 degrees
- left-right-rotation
- **optional:** bed extensions (644 mm) D 510FBVL
- LCD-speedometer

delivery content: tool test, 2x center point, optional tools, face plate



**YOUR
JOB.
OUR
TOOLS.**

D510F_230V

wood lathe



technical details

motor power s1 in W	735
total dimensions in mm	1060 (960) x 440(310) x 440
spindle taper	MK2 / MT2
lathe spindle speed in min-1	(1) 250-750(2) 550-1650(3) 1300-3850
distance between centers in mm	510
tailstock taper	MK2 / MT2
net weight in kg	55
packaging height in mm	320
packaging length in mm	990

voltage	230V / 50 Hz
spindle bore in mm	10
head stock spindle	M33
tailstock sleeve travel	90
center height in mm	160
sound pressure level in dB(A)	< 70
gross weight in kg	58
packaging width in mm	535
EAN code	9120058372377

**YOUR
JOB.
OUR
TOOLS.**