

ED300FD_230V

metal lathe

- serially equipped with leadscrew for thread cutting and automatic longitudinal feed
- induction-hardened and precision ground prismatic bed way guides
- hardened main spindle bedded with adjustable taper roll bearings
- high spindle centricity assures maximal turning accuracy
- spindle speed steplessly adjustable, speed can be read off conveniently from digital speed display
- comes with change gears delivering an exceptionally broad thread cutting range
- guides conveniently adjustable via V-ledges ensuring precision for many years
- powerful, low maintenance motor with undervoltage release
- smooth power transmission delivers constant torque
- tailstock can be adjusted for taper turning
- CW/CCW run mode

included in delivery: 3-jaw lathe chuck Ø 100mm, 4-way tool post, dead center MT3, dead center MT2, chuck guard, chip tray, change gears, tools



**YOUR
JOB.
OUR
TOOLS.**

ED300FD_230V

metal lathe



technical details

motor power s6 in W	630
voltage	230V
bed width in mm	100
spindle bore in mm	21
tailstock taper	MK2/MT2
lathe spindle speed in min-1	50-2500
range of inch threads	8-44
cross slide travel in mm	75
distance between centers in mm	300
net weight in kg	60
packaging height in mm	460
packaging length in mm	800
Search words	Drehmaschine lathe

motor power s1 in W	450
total dimensions in mm	740x390x370
carriage travel in mm	276
spindle taper	MK3/MT3
max. swing over cross slide in mm	110
range of metric threads in mm/r	(18 S) 0,5-3
tailstock sleeve travel	60
compound slide travel in mm	55
max. swing over bed in mm	180
gross weight in kg	65
packaging width in mm	480
EAN code	9120058371431

**YOUR
JOB.
OUR
TOOLS.**