

FKS305VF2600_400V

panel saw

-
- massive profi alu sliding table and extra long outrigger enables to handle big workpieces -
- perfect for cutting heavy large boards and plates
- equipped scoring unit powered by a separate motor
- compact control panel located at machine frontside for operation convenience
- smoothly running saw blade height and angle adjustment via hand wheel
- analog read out of saw blade adjustment (height and tilt)
- two different cutting speeds as standard
- high quality and stable machine body
- table extensions enable convenient working conditions
- double roller carriage aluminium sliding table with
- hardened steel guides,
- results in smooth running and highest precision
- heavy machine with massive, rugged but precise
- construction for max. cutting accuracy
- very accurate and solid rip fence with fine adjustment function
- extractable and solid mitre fence (1600-3150) at outrigger table incl. 2 end stops
- max. cutting width at parallel fence 1150mm



**YOUR
JOB.
OUR
TOOLS.**

FKS305VF2600_400V

panel saw



technical details

motor power s6 in W	7700
voltage	400V
table extension in mm	500x505 / 790x505
dust collector port in mm	100
outrigger table in mm	1110x610
max. trimming in mm	2600
max. cutting width at parallel fence in mm	1150
scoring sawblade in mm	Ø120
scoring unit speed in min-1	8000
sawblade swivel	0°-45°
gross weight in kg	680
packaging width in mm	1.070
EAN code	9120039909318

motor power s1 in W	5500
table size in mm	980x550
table height in mm	850
sliding table in mm	2600x375
max. cutting height 90° in mm	80
max. cutting height 45° in mm	55
sawblade in mm	305
sawblade speed in min-1	4500/5500
scoring unit motor power in W	750/1050
net weight in kg	580
packaging height in mm	980
packaging length in mm	2.250

**YOUR
JOB.
OUR
TOOLS.**